

Vanguard® Ground Mount 334 Equipment Cabinet Product Specifications



Cabinet Construction:	Aluminum 5052-H34 with continuously welded external seams
Access:	Three-point latch with stainless steel handle, two sides
Weight:	275 LBS. (125 kg) empty
Cabinet Dimensions:	5'6" H x 2'0" W x 2'6" D (1.68 m x 0.610 m x 0.762 m)
Cabinet Lock:	Corbin #2 lock
Door Opening Dimensions:	4'6" H x 1'10" W (1.372 m x 0.559 m)
Access Doors:	Sealed using 0.5" by 2" closed cell neoprene gasket
Ventilation:	Forced Air Ventilation
Controller:	Vanguard® Model VFC-3000
Cabinet Environmental Rating:	NEMA 3R
Lighting:	Fluorescent lamp located in top of cabinet
Power Requirements:	120/240 VAC, single-phase power (3 wire plus ground)
Equipment Rack:	One (1) EIA 19" rack

Notes:

1. The complete equipment cabinet contains one (1) support shelf, one (1) modem panel, one slide-out drawer, outlet panel, load center, internal fluorescent light with switch, forced air ventilation, all stainless steel hardware.
2. Consistent with Daktronics continuous improvement program, all product features are subject to change.